

CARRIED SPREADER MODEL SPR 6000-7000-8000-9000

Structure and materials

- Shell-bearing, sheet hopper, flat tail and fully rotating
Stainless steel AISI 304
- Commercial assembly bolts made of stainless steel
- rotating plate with manual adjustment for asymmetric spreading
- Tail height adjustable and folding up during their transfer
(Tipping working trough telescopic gas springs)

Spreading system

Spreading of material with tape made of honeycomb stainless steel
AISI 316 – fan spreading rear tail and rotating plate spreading fan (width and asymmetry adjustable)

Operation

Through vehicle hydraulic system, or alternatively, by independent hydraulic system with an auxiliary gasoline and diesel engine

Control panel

Control box with electrical cable, in the cab, with the following functions:
On / Off auxiliary engine (when available), On / Off spreading, On / Off lights and for quantity and width spread (optional)

Optional

Net (or protection grid), yellow flashing light, panel with left side arrow, PVC cover, parking feet, salt sensor, ECO-SAL computerised push button panel, inspection ladder, xenon light, pair vibrators fibreglass rear cabinet , repeater rear bar

Technical data

Hopper capacity 6000 lt - 7000 lt - 8000 lt - 9000 lt
weight (empty)..... from 1000 to 1600 kg
Spreading width 2 ÷ 24 mt